

HOUSEHOLD DEHUMIDIFIER

MiniDry 160

Provided with:

- Electronic Control
- Display LCD
- Elegant and refined design

Peculiarities:

- Very compact and light
- Two speed fan
- Low Power Consumption
- Handle and 4 pivoting wheels
- Reciprocating compressor

Used mainly in:

- Houses, Kitchen
- Laundries
- Shops
- Libraries



TECHNICAL DATA:

Rated Maximum Power absorbed (at 20°C, 60% R.H.)	160 W
Rated Maximum Power absorbed (at 35°C, 95% R.H.)	260 W
Max. Current Absorbed (at 35°C, 95% R.H.)	1,9 A
Air Flow	160 mc/h
Sound Pressure Level (at 3 mts in free field)	36 db(A)
Refrigerant	R134a
Defrosting Control System	elettronic
Capacity of Condensed Water Tank	2 Lt
Functioning Temperature Range	7-35 °C
Functioning Relative Humidity Range	50 - 99 %
Rated Condensation Capacity (at 30°C - 80 %)	10 l/ 24h
Rated Condensation Capacity (at 32°C-90 %)	12 l/ 24h
Weight with empty tank	9 kg
Dimensions LxDxH mm	292x264x476
Dimensions with Packaging Carton Boxes LxDxH mm	362x282x508
Number of Units in 40' (20') container	circa 1092 (532)
Voltage Available:	230/1/50

CONDENSED HUMIDITY AT DIFFERENT TEMPERATURES AND R.H. CONDITIONS

Room conditions	Condensed Water
10°C - 60%	1 l/24h
10°C - 80%	2 l/24h
15°C - 60%	1,5 l/24h
15°C - 80%	2,5 l/24h
20°C - 60%	2,5 l/24h
20°C - 80%	4 l/24h
25°C - 60%	4 l/24h
25°C - 80%	5 l/24h
27°C - 65%	4 l/24h
27°C - 80%	6 l/24h
30°C - 80%	10 l/24h
32°C - 80%	12 l/24h

Data sheet MiniDry 160