



Centrifugal Atomiser DG

for direct room humidification

Mount the HygroMatik Atomiser DG for direct room humidification directly on production hall or storage room ceilings. It generates a fine water mist and its powerful integrated fan distributes this evenly to the ambient air. This creates an additional cooling effect. The DG has a very low energy consumption and works without water losses.



- Humidification capacity 4-8 l/h
- Operates with fresh water, therefore no water losses
- Additional cooling effect
- Very low electrical energy consumption
- Simple and quick maintenance
- Full 360° degree humidification

HygroMATIK
MORE THAN
45 YEARS
HUMIDIFICATION



Humidification for best conditions.



Technical Data for Centrifugal Atomiser DG

Type	DG4	DG 8
Humidification capacity [kg/h]	4	8
Effective volume ** [m ³]	400	1200
Circulation air [m ³ /h]	350	600
Motor power rate [kW]	0,14	0,16
Electrical supply *	230V/ 50 Hz/1N	400 V/50 Hz/3N
Nominal current [A]	0,65	0,58
Diameter [mm]	450	620
Height [mm]	280	390
Water supply		
Feed [bar]	1-6	1-10
Safety overflow	R 1/4"	R 1/4"
	R 1/2"	R 1/2"
Empty weight [kg]	4,5	15
Operational weight [kg]	5	15,5

* Other voltages on request.

** Varies depending on room temperature and required room humidity.

Subject to technical amendments without notice.

HygroMATIK
WE HUMIDIFY THE AIR

HygroMatik GmbH
Lise-Meitner-Str. 3
24558 Henstedt-Ulzburg
Germany

T +49 4193 895-0
F +49 4193 895-33
hy@hygromatik.de
www.hygromatik.com

A member of the **spirax**/**sarco** group

