



## CENTRIFUGAL FANS

### SERIES FKS

- Fan casings are from robust galvanized sheet steel finished with electrostatic paint coating.
- Impellers are forward curved "sirocco type"
- Motors could be 230V/50Hz or 400V/50Hz.
- Motor speed 900RPM, 1400RPM, 2800RPM.
- IP:55 protection.
- Class F insulation.



450 - 3.200 m<sup>3</sup>/h

**APPLICATIONS:** Various ventilation applications including motor cooling etc.

**ELECTRICAL ACCESSORIES:** Speed controllable in 230V with REB-5000W and in 400V with INVERTER.

**UPON REQUEST:** The fan can be placed inside an acoustic box. The color is upon request.

**FKSB=230V/50Hz FKST=400V/50Hz /2=2800RPM /4=1400RPM**

TYPE	HP	Inlet diameter Ømm	Motor speed rpm	AIR FLOW m <sup>3</sup> /h	VOLT	PRICE €
FKSB/2-100/025	0,25	100	2800	450	230	
FKSB/2-120/025	0,25	120	2800	800	230	
FKST/2-120/025					400	
FKSB/2-120/050	0,50	120	2800	1.600	230	
FKST/2-120/050					400	
FKSB/2-140/075	0,75	140	2800	2.500	230	
FKST/2-140/075					400	
FKSB/2-160/150	1,50	160	2800	3.500	230	
FKST/2-160/150					400	
FKSB/2-180/200	2,00	180	2800	3.200	230	
FKSB/2-180/200					400	

TYPE	HP	Inlet diameter Ømm	Motor speed rpm	AIR FLOW m <sup>3</sup> /h	VOLT	PRICE €
FKSB/4-120/025	0,25	120	1400	450	230	
FKST/4-120/025					400	
FKSB/4-120/033	0,33	120	1400	900	230	
FKST/4-120/033					400	
FKSB/4-140/033	0,33	140	1400	1.250	230	
FKSB/4-140/033					400	
FKSB/4-160/050	0,50	160	1400	1.750	230	
FKST/4-160/050					400	
FKSB/4-180/050	0,50	180	1400	2.550	230	
FKST/2-180/200					400	

